

# Product data sheet


NORA III (BEADED)  
9.773.3062.06  
LEIPZIGER LEUCHTEN



IP  
55

For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier , painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of supply includes special steel post bracket, painted -Order post dia. 60 mm/ dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



### 1 x High pressure mercury vapour lamp

Nominal lamp power	125 W	LOR	73%
Lamp flux	6800 lm	ULOR	3%
Luminous efficacy	36 lm/W	Total flux	4976 lm
CCT	3400 K	Total power	137 W
CRI	54		

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 11.81 in

Diameter: 21.26 in

## Electric

System power: 137 W

## Protection

IP: 55