

Product data sheet


DEFINE LED SUSPENDED LUMINAIRE
S122DIP-S485D530U835-4F0-1E-UDD-A1
COOPER LIGHTING



IP
47

Surface mount slot family in 2", 3", 4" and 5" housing sizes, Specifiable to the nearest 1', Multiple lensing options: flush satin, drop, regressed and asymmetric, Multiple lumen packages, 0-10V dimming standard; DALI dimming available, 2700K, 3000K, 3500K, 4000K and 5000K correlated color temperatures, VividTune CCT tuning options from 3000K–5000K or 2700K-6500K, Integral Wavelinx, Lumawatt Pro and stand-alone sensors available, Customizable in-wall, in-ceiling and wall-to-ceiling corners available, DLC listed configurations available

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 3500 K |
| Nominal lamp power | 32.8 W | CRI | 80 |
| Total flux | 4036 lm | LOR | 100% |
| Luminous efficacy | 123 lm/W | ULOR | 47% |
| | | Total power | 32.8 W |

Mounting mode

Pendant

Shape and measurements

Length: 48.00 in

Width: 2.00 in

Height: 0.39 in

Adjustability

Fixed

Electric

System power: 32.8 W

Protection

IP: 47