

Product data sheet


MOD*O L50 E3
MOD OFFICE EMERGENCY
DEXTRA



IP
20


MOD Office - 600x600, IP40 Recessed luminaire, white powder coated one piece steel body, with central microprism optic with high transmission opal diffuser surround. Replace * with P for Pull-up or R for Lay-in. Options: E3 - Emergency control gear (390 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* H - High Frequency Dimming (Analogue 1-10v) R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless occupancy and daylight dimming RLS - Reacta-Link Wireless Presence & Daylight Sensor RCS - Reacta-Control Wireless, Presence 4PM - 4 Pole panel mount 6PM - 6 Pole panel mount MODRS TETHER KIT - Secondary fix single drop MODRS TETHER KIT TWIN-Secondary fix twin drop

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	30.9 W	CRI	80
Total flux	3711 lm	LOR	100%
Luminous efficacy	120 lm/W	ULOR	4%
		Total power	30.9 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4.3 W	CRI	80
Total flux	390 lm	LOR	100%
Luminous efficacy	91 lm/W	ULOR	4%
		Total power	4.3 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.62 in

Width: 23.62 in

Height: 2.83 in

Electric

System power: 35.2 W

Ballast: ECG

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 20