Product data sheet

VOL Ø135 MM 90-4881-14-M3

LEDSC4








LedsC4 Vol Ø135 mm 90-4881-14-M3V2 Downlight for indoor use. For downlighting. Structure material: Aluminium. Structure finish: White. Diffuser material: Methacrylate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 0 Product width or diameter (mm): 135 Product height (mm): 50 Ø of the hole for recessing (mm): 117 Permitted ceiling thickness: 0-25 Class 2. Luminaire not suitable for coating with insulation materials. IP: IP54. IK: IK08. LED. No. of lampholders or LEDs: 1. LED brand: SAMSUNG. Driver brand: VOSSLOH-SCHWABE. Maximum power of light source: 8.4W. Colour temperature: 4000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L70B30. UGR: 23.7. Photobiological risk: RG1. Real flux (lm): 888. Nominal flux (lm): 1095. Real lm/W: 83. Voltage / frequency range: 100-240/50-60Hz. Voltage: 3. Equipment included: Yes. Total power: 10.7. Power factor: 0.81. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED	
Nominal lamp power	10.3 W
Lamp flux	888 lm
Luminous efficacy	86 lm/W
CCT	4000 K
CRI	80

LOR	100%
Total flux	888 lm
Total power	10.3 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 5.31 in Width: 5.31 in Height: 0.08 in

Adjustability

Fixed

Electric

System power: 10.3 W Appliance Class: II

Protection

IP: 54 IK: 08

Designation labels: CE