Product data sheet

PH 2/1 WALL E14 LED 2700K 5W 5743141629

LOUIS POULSEN








PH 2/1 Wall Design: Poul Henningsen Concept: The fixture is designed based on the principle of a reflective three-shade system, which directs the majority of the light downwards. The shades are made of mouth-blown opal three-layer glass, which is shiny on the top and sandblasted matt on the inside, giving a soft and diffuse light distribution. Finish: White opal glass. High lustre chrome plated. Material: Shades: Mouthblown white opal glass. Wall box: High lustre chrome plated, spun brass. Suspension: High lustre chrome plated, spun aluminium. Arm: High lustre chrome plated, brass. Mounting: Cable length: 2.9m. Light control: On wall plate. Class: Ingress protection IP20. Electric shock protection II w/o ground. Weight: Max. 1.5kg.

Light output 1



1 x LED			
Nominal lamp power	5 W	LOR	71%
Lamp flux	470 lm	ULOR	13%
Luminous efficacy	66 lm/W	Total flux	332 lm
CCT	2700 K	Total power	5 W
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Height: 6.50 in Diameter: 7.87 in

Adjustability

Fixed

Electric

System power: 5 W Appliance Class: I

Protection

IP: 20