Product data sheet

SMART KUP 82 IP55 LED GE 3000K FLOOD BLACK STRUC 12472432

MODULAR









Smart lighting family Smart Cake, Smart Lotis and Smart Kup are Modular's new generation minispots. They combine technical ingenuity with timeless design. The names speak for themselves. The design of these mini-spots is based on Modular's most popular designs. What you get is a LED module with a different finish. The design of the Smart Kup looks like a flaring cylinder.

Light output 1




| 1 x LED | |
|--------------------|---------|
| Nominal lamp power | 13.4 W |
| Lamp flux | 994 lm |
| Luminous efficacy | 61 lm/W |
| CCT | 3000 K |
| CRI | 90 |
| | |

| LOR | 82% |
|-------------|--------|
| Total flux | 815 lm |
| Total power | 13.4 W |
| | |



| 1 x LED | |
|--------------------|---------|
| Nominal lamp power | 6.2 W |
| Lamp flux | 576 lm |
| Luminous efficacy | 76 lm/W |
| CCT | 3000 K |
| CRI | 90 |

| LOR | 82% |
|-------------|--------|
| Total flux | 472 lm |
| Total power | 6.2 W |



| 1 x LED | | | |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 9.2 W | LOR | 82% |
| Lamp flux | 773 lm | Total flux | 634 lm |
| Luminous efficacy | 69 lm/W | Total power | 9.2 W |
| CCT | 3000 K | | |
| CRI | 90 | | |

Mounting mode

Ceiling recessed

Electric

System power: 6.2-13.4 W Appliance Class: II

Shape and measurements

Height: 0.39 in Diameter: 3.23 in

Adjustability

Fixed

Protection

IP: 55