
Product data sheet


PATH
55-E034-14-CL
LEDSC4



IP 67 IK 10

LedsC4 Path 55-E034-14-CL Lineal lighting system for outdoor use. For downlighting. Includes 2 cable outlets to facilitate chain mounting. Metres of cable included: 0.15. Structure material: Aluminium. Structure finish: White. Diffuser material: Methacrylate. Diffuser finish: Opal. UV protection. Warranty: 5 Years. Max. temperature: 50ºC. Product net weight (Kg): 2.08 Product length (mm): 1004 Product width or diameter (mm): 61 Product height (mm): 68 Class 3. IP: IP66-IP67. IK: IK10. LED. No. of lampholders or LEDs: 1. Maximum power of light source: 9.6W. Colour temperature: 3000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 19.6. Photobiological risk: RG0. Real flux (lm): 184. Real lm/W: 19. Voltage: 3. Equipment included: No, but it is needed. Total power: 9.6.

Light output 1



1 x LED

Nominal lamp power	10.14 W	LOR	100%
Lamp flux	184 lm	Total flux	184 lm
Luminous efficacy	18 lm/W	Total power	10.14 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted, Standing / Bollard

Shape and measurements

Length: 39.37 in
Width: 2.40 in
Height: 2.60 in

Adjustability

Fixed

Electric

System power: 10.14 W
Appliance Class: III

Protection

IP: 67
IK: 10