# Product data sheet

C95-S240X1200 LED 3000 830 MP

GLAMOX



IP 20

Light source LED: 3000-6300lm out. 3000/4000K, CRI 80 or 90. MacAdams 3. CCT-version: 4800lm out, 2700-6500K CRI 80. Lifetime LED: Up to 100.000h Ta25. Minimum 50 000h Max Ta. For precise technical information please see the data sheet on item level. (Use <Find your version> on right side) Driver HF or DALI Body material & colour Body frame in white anodized aluminum with steel plate on top. Body in anodized aluminum is available on request. Mounting Mounted direct to the ceiling thru 4 mounting key holes on top. Connection Cable entry in top or knockouts in each end. 3 or 5 pole push-in terminal block. Optics Micro prismatic (MP) or Opalic (OP). C95-S600x600 is also available in a version (IND) that gives a little indirect light in the ceiling. Sensors Daylight and presence sensor (D2-SEN) or stand-alone presence sensor type S-SEN. Emergency system Standard (S), Self test (ST) or DALI. 1h or 3h.

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 22 W | CRI | 80 |
| Total flux | 3061 lm | LOR | 100% |
| Luminous efficacy | 139 lm/W | ULOR | 84% |
| | | Total power | 22 W |

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 47.01 in
Width: 9.21 in
Height: 2.05 in

### Adjustability

Fixed

### Electric

System power: 22 W

### Protection

IP: 20