
# Product data sheet

STORMBELL 80 SU SF 1500 WW MFL BK/WH+ ACC. BELL STORMBELL 80 Ø363X60 WH ST18SSLOMF930NBW+S8BE363W


LAMP





Downlight to suspend model STORMBELL 80 SU SF 1500 WW MFL BK/WH LAMP brand. Body made of injected aluminum with white/black/Materiality finish, and with black/opal polycarbonate ring, for decorative lighting effect and possibility of accessory color filter, depending on his model. COB LED 3000K color temperature and CRI90. Aluminium reflector MEDIUM FLOOD. Luminaire with ceiling rose and electronic equipment included. Insulation class I. LED life time: 50000 L90 B10. Compatible with 4 different models of bells (accessories) that complete the luminaire. + Accessory for suspended luminaries modell ACC. BELL STORMBELL 80 Ø86x50 WH LAMP brand. Body made of aluminum with white/black/Materiality finish. + Accessory for suspended luminaries modell ACC. BELL STORMBELL 80 Ø363x60 WH LAMP brand. Body made of aluminum with white/black/Materiality finish.

#### Light output 1



### **1 x LED** Nominal lamp power Lamp flux Luminous efficacy CCT CRI

14.1 W 1331 lm 94 lm/W 4000 K 90

LOR Total flux Total power 100% 1327 lm 14.1 W

## Mounting mode

Pendant

#### Shape and measurements

Height: 2.36 in Diameter: 14.29 in

#### Adjustability

Fixed

#### Electric

System power: 14.1 W Appliance Class: I

#### Protection

IP: 20