


Product data sheet

RWYC 1500 L22 MP LE3
RUNWAY CURVE EMERGENCY
DEXTRA




Runway Curve - 1500mm Surface/suspended linear luminaire, extruded aluminium trunking with painted finish and microprism diffuser.
Options: LE3 - Lithium Emergency (360 lumens output) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* RC - Reacta-Control Wireless Module RCS - Reacta-Control Wireless, Presence RLI - Reacta-Link Wireless Module GY - Grey Finish WH - White Finish BL - Black Finish RWY SUSP 3M BF x1- Runway 3M single point suspension kit RWY SMK - Runway Surface Mount kit (single point) RWYC INSTALL KIT - Runway Curve Installation Kit (1 Kit per installation)

Light output 1



1 x LED			
Nominal lamp power	12 W	LOR	100%
Lamp flux	1589 lm	ULOR	4%
Luminous efficacy	132 lm/W	Total flux	1589 lm
CCT	4000 K	Total power	12 W
CRI	80		

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	3 W	CRI	80
Total flux	360 lm	LOR	100%
Luminous efficacy	120 lm/W	ULOR	4%
		Total power	3 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 60.59 in
Width: 2.56 in
Height: 3.74 in

Glare protection

Glare protection: UGR < 19

Electric

System power: 15 W
Ballast: ECG
Controller: DALI

Adjustability

Fixed

Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor, Presence sensor

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20

Designation labels: CE