

# Product data sheet


LED IT STRIP  
982522.002  
RZB



IP  
65

Series: LED it Strip Type of Protection: IP 65 Voltage: 24 V / 0 Hz Flexible fully encapsulated LED strip for indoor and outdoor use. UV/IR resistant TPU potting. Solderless connection technology by means of plug &Play connector system. Easy separability with commercially available tools. every 130 mm. Up to 5 meters LED strip length with only one power supply. Supply voltage 24 V DC, 12 W/m, 1100 lm/m (950 lm/m at 3000 K). 7 LEDs per segment, LED pitch 18 mm. Smallest bending radius 60 mm. Operating temperature from -20 °C to 50 °C. One power supply and one End cap included, other accessories can be ordered separately. Available Colours: white Dimensions: L 5000, B 12, H 3 Lamp: LED Life time: 35000 h Colour Temperature: 3000K Socket 1: without socket Luminaire flux LED: 4750lm System power: 60W Beam Angle: 107° Unified Glare Ratio: 25,4

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	60 W	CRI	80
Total flux	4750 lm	LOR	100%
Luminous efficacy	79 lm/W	Total power	60 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 0.47 in  
Width: 39.37 in  
Height: 0.16 in

## Adjustability

Fixed

## Electric

System power: 60 W

## Protection

IP: 65