# Product data sheet

TOP MINI W/O EQ. 30° 2700K WT A2960020WT

**ARKOSLIGHT** 





Top is a miniaturized surface-mounted ceiling luminaire. Its compact design makes Top an ideal solution for installation in ceiling cavities and for projects where a discrete presence of the luminaire in the scene is desired. Formally Top presents itself as a design of pure lines and architectural aesthetics. In terms of lighting, Top offers a conical distribution with three available beam angles (flood, medium and spot). Its installation is extremely easy and safe, fixing it to the ceiling by means of a bayonet system that does not require the use of any tools.

### Light output 1



| I x LED            |         |
|--------------------|---------|
| Nominal lamp power | 6.5 W   |
| Lamp flux          | 610 lm  |
| Luminous efficacy  | 94 lm/W |
| CCT                | 2700 K  |
| CRI                | 90      |
|                    |         |

| LOR         |   | 89%    |
|-------------|---|--------|
| Total flux  | Ę | 543 lm |
| Total power |   | 6.5 W  |
|             |   |        |

# Mounting mode

Ceiling mounted, Wall recessed

## Shape and measurements

Length: 1.57 in Width: 1.57 in Height: 1.85 in

# Adjustability

Fixed

### Electric

System power: 6.5 W

### Protection

IP: 20