


# Product data sheet

STYLE II 21011 LED O CG-S  
40071356816  
EATON EMERGENCY LIGHTING



• Compact safety luminaire from high quality, UV-resistant, halogen-free plastic with LED-technology • Modular constructed luminaire series permits combination with various fixing modules • Available in two different optical variants: • Symmetrical light distribution for mounting heights up to 9 m • Minimum service requirement due to high service life of the LEDs (up to 50,000 hours) • Simple mounting via quick mounting set (can be pre-assembled) with plug-in connectors for through-wiring • Ingress protection IP54 for increased sealing requirements both indoor and in protected outdoor areas • Shortened inspection effort due to CEWA GUARD technology • Automatic function monitoring of up to 20 luminaires per circuit • Reduced installation expenditures by STAR technology • Freely programmable mixed operation of the switching modes per luminaire in one circuit

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	5.8 W	CRI	70
Total flux	102 lm	LOR	100%
Luminous efficacy	18 lm/W	Total power	5.8 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 4.65 in  
Diameter: 2.36 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray

## Electric

System power: 5.8 W  
Appliance Class: II

## Information regarding emergency functions

Emergency lighting only  
Emergency power supply: Central battery feed-in  
Emergency sign: N/A

## Protection

IP: 54  
IK: 03