



Product data sheet

ARIZONA LARGE 3 LIGHT COLUMNS
AR-20991-LC-N-W40
LIGMAN




· Lamp LED · CRI Ra > 80 · MacAdam Ellipse 3 SDCM · Colour 3000K and 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector or PMMA lens - Clear, acrylic PMMA diffuser - Maximum wind load resistance is 140 km/h - Surge protection 10 kV

Light output 1 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	12.1 W	CRI	80
Total flux	544 lm	LOR	100%
Luminous efficacy	45 lm/W	Total power	12.1 W

Light output 2 (integrated)




Lamp type	LED	CCT	4032 K
Nominal lamp power	12.1 W	CRI	80
Total flux	544 lm	LOR	100%
Luminous efficacy	45 lm/W	Total power	12.1 W

Light output 3 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	12.1 W	CRI	80
Total flux	544 lm	LOR	100%
Luminous efficacy	45 lm/W	Total power	12.1 W

Light output 4 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	12.1 W	CRI	80
Total flux	544 lm	LOR	100%
Luminous efficacy	45 lm/W	Total power	12.1 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 52.95 in

Diameter: 8.86 in

Weight: 18.5 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 48.4 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 65

IK: 08

Surface temperature: 40°C