Product data sheet


SPOT 2.6 316L L [3000K 6W 24VDC]
PW26005LI
L&L LUCE&LIGHT



IP 68 IK 10

Projector for outdoor and underwater applications; surface mounted (ceiling, wall, ground, stake), max depth 10 m; body and trim in AISI 316L stainless steel, screen in tempered glass; 3 power LEDs; 6W (3 power LEDs x 2W) - 24Vdc; includes 5 m neoprene cable H05RN-F 2x0,75/0,75 Ø6,3 mm; total delivered lumens: 314 lm (3000K); optics: 10°, 24°, 38°; LED colour: white - 2700K, 3000K, 4000K, 5000K; blue; ingress protection: IP68; impact resistance: IK10; equipped with IPS; operating temperature: -10°C +45°C; screen temperature: max 30°C (Ta 25°C); Glow wire test: 960°; photobiological safety: risk group 1 in accordance with EN62471:2006; appliance class: III; weight 1,00 kg; dimensions Ø69x60mm, h 135 mm; dimming using a 24Vdc dimmer; accessories: stake WP0100

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6 W	CRI	80
Total flux	280 lm	LOR	100%
Luminous efficacy	47 lm/W	Total power	6 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 1.08 in
Width: 0.98 in
Height: 2.42 in

Adjustability

Free

Electric

System power: 6 W
Appliance Class: III

Protection

IP: 68
IK: 10