

# Product data sheet

AMEX L16 EB  
AMENITY EXTERIOR LED  
DEXTRA




IP  
65

IK  
08

Amenity Exterior - IP65, IK08 Surface mounted Exterior Luminaire, die cast aluminium body with eyelid, finished in black powder coat paint, opal polycarbonate diffuser. Options: LE3 - Lithium Emergency (164 lumens) LS3 - Lithium Selftest LA3 - Lithium Autotest A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)\* S - Switch Dimming D - Digital Dimming (DSI) R25E - Reacta 25, On / Off High Frequency R25C - Reacta 25, Corridor Mode\* RLM - Reacta-Link Wireless Microwave Presence & Bright Out RCME - Reacta-Control Wireless Microwave On/Off RCMC - Reacta-Control Wireless Microwave Corridor Mode\* \*Bi-Level Dimming. Will only dim the luminaire to 10% during absence and brightout, it will not turn the luminaire off.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	11.8 W	CRI	80
Total flux	930 lm	LOR	100%
Luminous efficacy	79 lm/W	ULOR	4%
		Total power	11.8 W

## Mounting mode

Ceiling mounted, Wall mounted

## Electric

System power: 11.8 W

## Shape and measurements

Height: 4.61 in  
Diameter: 14.17 in

## Protection

IP: 65  
IK: 08

## Adjustability

Fixed