


Product data sheet

CIRCULAR OUTWARD 5 RINGS (Ø600 Ø1200 Ø2000 Ø1200 Ø600)
CF4F-00W9AZRUEF
LEDSC4




LedsC4 Circular Outward 5 Rings (ø600 ø1200 ø2000 ø1200 ø600) CF4F-00W9AZRUEFV1 Pendant for indoor use. For sideways lighting. Structure finish: Gold. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 0 Product width or diameter (mm): 2042 Product height (mm): 5500 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 330.8W. Colour temperature: 3000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG1. Real flux (lm): 27873. Real lm/W: 82. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 340. Power factor: 0.90. Dimmable equipment included: 0-10V.

Light output 1




1 x LED			
Nominal lamp power	37.4 W	LOR	100%
Lamp flux	3402 lm	ULOR	50%
Luminous efficacy	91 lm/W	Total flux	3403 lm
CCT	3000 K	Total power	37.4 W
CRI	90		

Light output 2




1 x LED			
Nominal lamp power	37.4 W	LOR	100%
Lamp flux	3402 lm	ULOR	50%
Luminous efficacy	91 lm/W	Total flux	3403 lm
CCT	3000 K	Total power	37.4 W
CRI	90		

Light output 3




1 x LED			
Nominal lamp power	69.3 W	LOR	100%
Lamp flux	5663 lm	ULOR	49%
Luminous efficacy	82 lm/W	Total flux	5664 lm
CCT	3000 K	Total power	69.3 W
CRI	90		

Light output 4



1 x LED			
Nominal lamp power	126.6 W	LOR	100%
Lamp flux	9743 lm	ULOR	49%
Luminous efficacy	77 lm/W	Total flux	9745 lm
CCT	3000 K	Total power	126.6 W
CRI	90		

Light output 5



1 x LED			
Nominal lamp power	69.3 W	LOR	100%
Lamp flux	5663 lm	ULOR	49%
Luminous efficacy	82 lm/W	Total flux	5664 lm
CCT	3000 K	Total power	69.3 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 23.62 in

Width: 23.62 in

Height: 1.18 in

Adjustability

Fixed

Electric

System power: 340 W

Appliance Class: I

Protection

IP: 20