


Product data sheet

PENDANT LUMINAIRE SOLO SLIM OFFICE L2 101W CRI > 80 3000K S
2004.4250 - SOLO SO PEN980-3000 LED14900-830 DID SR DALI
REGENT



Pendant luminaire Solo Slim Office with LED, system power: 101 W, standby power 0.5 W, luminous flux of luminaire 14900 lm, colour rendering index CRI > 80, 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 (UGR < 19; Lmax ≥ 65° ≤ 3000 cd/m²), photobiological safety: the luminaire poses no danger (RG0), 230 V, nominal current: 2.3 A, direct-indirect light emission, frame in aluminium silver, neat shadow gap, diffuser in polymethyl methacrylate (PMMA) office-suitable microprismatic CLD optics (Controlled Luminance Diffusor) for perfect glare control, 1 integral control gear, DALI, pendant suspension kit to be ordered separately, ENEC certified, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0318), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP40, glow wire test 650 °C, impact strength: IK 06, this product contains a light source of energy efficiency class D Ø = 980 mm, H = 78 mm, p = 3000 mm

Light output 1



1 x LED			
Nominal lamp power	60 W	LOR	100%
Lamp flux	14900 lm	ULOR	40%
Luminous efficacy	248 lm/W	Total flux	14902 lm
CCT	3000 K	Total power	101 W
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 38.58 in
Width: 38.58 in
Height: 3.11 in
Weight: 16.628 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 101 W

Appliance Class: I

Protection

IP: 40

IK: 06