


Product data sheet

LP SLIM ROUND SUSPENDED Ø680 WHITE LED KA 48W PRISM
91712-1002
LOUIS POULSEN



LP Slim Round Design: Louis Poulsen A/S Concept: The slim housing encircles and high-efficient acrylic diffuser emitting diffused primarily downward directed light. The slim body has a slight curvature and an inner curve which reduces contrast. The product family comes in a range of sizes and mounting options for a wide range of applications. Surface mounted and suspended versions have an indirect light component. Finish: White, aluminium grey or black, powder coated. Material: Reflector: Die cast aluminium. Diffuser: Acrylic, opal. Installation lock: Aluminium. Mounting: Ceiling thickness: 1–60 mm. Cut-out dimensions Ø 250: Ø234mm Ø 440: Ø425mm Ø 680: Ø 666mm. Optional wire for alternative installation. Looping: Approved, max 5x1.5mm². Driver integrated. Weight: Max: 8.8 kg Class: Ingress protection IP20. Electric shock protection I.

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 57 W | CRI | 90 |
| Total flux | 4767 lm | LOR | 69% |
| Luminous efficacy | 84 lm/W | Total power | 57 W |

Mounting mode

Pendant

Shape and measurements

Height: 1.85 in

Diameter: 26.77 in

Adjustability

Fixed

Electric

System power: 57 W

Appliance Class: I

Protection

IP: 20