Product data sheet

SRT-SYSTEM IP64-SRGSCB PP/1500 LED - GERÄTETRÄGER FIX CENTRAL.LINE.OPTIC | DEVICE MOUNT FIX CENTRAL.LIN.. 4000 865 IP64 ET VW RAL 9016 (SRT+19512004150)


REGIOLUX



IP 64 IK 03 CE

SRT-Quick-fit mounting system, IP 64 device mount, Modullänge/1500. Device mounts made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantees good corrosion protection; tool-free attachment with design-integrated push locks ensure protection against theft and disassembly. Integrated end faces made of plastic with sealing lips and an all-round closed seal to the support rail for a protection type up to IP64. Housing colour traffic white RAL 9016. Performance level: Powerful Performance (PP) - Powerful, universal all-rounder, sets very high standards for efficiency, service life and warranty period, Light distribution direct wide distribution by means of Central.Line.Optic of PMMA plastic, The lens optics ensure ease of installation and are easy to maintain thanks to the easy-to-clean surface. The density of the single-row lens arrangement ensures that the points merge into a line with a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a fixed, 3-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Dimensions (LxWxH): 1535mm x 55mm x 37mm Beam angle: 95°(C0)/100° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 6500K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG1 LED service life: 75000h L80/B10 (Tq 45°C), 100000h L80/B50 (Tq 45°C) Nominal luminous flux: 4425lm Luminaire luminous efficiency: 186lm/W Control gear: Electronic driver (1 pcs.) System output: 24W Energy efficiency class/light source: B Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (-20°C bis 45°C) Ambient temperatur: ta -20°C to 45°C UGR lat./long.: 20.6 / 22.0 Certification mark: IP64, Protection class I, ENEC10 VDE, F, D, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 7 years Regiolux GmbH Type: SRGSCB PP /1500 LED 4000 865 ET vw RAL 9016 Article number: 19512004150 Product deep link: https://www.regiolux.de/en/article/19512004150 General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	6500 K
Nominal lamp power	23.8 W	CRI	80
Total flux	4425 lm	LOR	100%
Luminous efficacy	186 lm/W	Total power	23.8 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 60.43 in
Width: 2.48 in
Height: 2.64 in

Electric

System power: 23.8 W
Appliance Class: 0

Protection

IP: 64
IK: 03
Designation labels: CE, ENEC

Design

Color of housing: White