

Product data sheet

LED MULTI PANEL 24W 3000K/ 4000K /6500K

MRPL-24/3C


MPE



IP
20

- Round shape - Recessed or surfaced installation. - The light has 3 color modes: Warm White-Cool White-Natural - Driver is integrated inside the light. - There are 5 matching color borders - Size: Ø290 x 15 mm - Hole diameter is adjustable: Round hole diameter: Ø60 - Ø250mm Square hole diameter: 60 x 60mm - 190 x 190mm - Voltage: 170-265VAC - Power: 24W - Power Factor (PF): >0.5 - Luminance: 2500 lm - Color Temperature (CCT): 3000K/4000K/6500K - RA >80 High Color Rendering Index - Beam angle: 120° - Chip LED: SMD 2835 - Life Time: 30,000 hours - Instant Light: 0s - European Standard CE - RoHS

Light output 1



1 x LED Module

Nominal lamp power	24 W	LOR	120%
Lamp flux	5200 lm	Total flux	6264 lm
Luminous efficacy	261 lm/W	Total power	24 W
CCT			
CRI			

Mounting mode

Ceiling mounted

Shape and measurements

Height: 0.59 in

Diameter: 11.42 in

Adjustability

Fixed

Electric

System power: 24 W

Color adjustable

Protection

IP: 20