Product data sheet

LINEAR LIGHTING

V1-R0-00034-80OPD-2003640 G-LINE 1,2 M WITH DIFFUSER 36W 4000K DALI


VARTON



IP 20 IK 01

• Recessed luminaire made of extruded aluminum • Standalone or continuous lines • Suitable for through-wiringFlexible modular system for different shapes Application • Offices • Commercial spaces • Administrative facilities • Retail spaces Installation • Recessed mounted solution Input voltage (AC, 50Hz), V: 176...264 Power factor: 0,95 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Color rendering index: 80-89 Protection class: I Mounting method: Built-in Ingress protection (IP): IP20 Radiation angle, °: 100 Impact resistance: IK01 https://www.varton.ru/products/lineynye-svetilniki-dlya-vnutrennego-osveshcheniya/g-line/g-line-1-2-m-s-rasseivatelem/svetodiodnyy-svetilnik-varton-g-line-1130kh100kh80-mm-36-vt-4000-k-s-opalovym-rasseivatelem-dimmirue/

Light output 1



1 x LED

Nominal lamp power	36 W	LOR	100%
Lamp flux	3600 lm	Total flux	3601 lm
Luminous efficacy	100 lm/W	Total power	36 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 44.49 in
Width: 3.94 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 36 W

Protection

IP: 20
IK: 01