



Product data sheet

ROUNDED MIDI
582003.0031.19
RZB



Series: Rounded Midi Type of Protection: IP 66 Protection Class: I Voltage: 220 - 240 V / 50 Hz Housing made of corrosion-resistant pressure die-cast Aluminium for outdoor use, powder coated. Opal plastic (Polycarbonate) spherical cap diffuser retained in cover ring. Screwless cover fixing via bayonet lock with safety catch. Base fixing slots outside of gasketed volume, drill hole deviations can be compensated. Standard with mains voltage LED module and Integral HF movement sensor. Mains connection 2x 3x 1,5 mm². Available Colours: anthracite metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 268, H 91 Lamp: LED Life time: 45000 h (L70/B50) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 360lm System power: 10W Beam Angle: 105° Unified Glare Ratio: 18,8 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10 W	CRI	80
Total flux	360 lm	LOR	100%
Luminous efficacy	36 lm/W	ULOR	3%
		Total power	10 W

Mounting mode

Wall mounted

Shape and measurements

Height: 3.58 in

Diameter: 10.55 in

Adjustability

Fixed

Electric

System power: 10 W

Protection

IP: 66

IK: 10