


# Product data sheet

PURE 1  
09.1610/HI-PAR/35W/24°38°60°  
FLOS




Recessed luminaire for indoor application. For very low voltage halogen lamps or standard and discharge lamps. Self-extinguishing ceramic or engineering plastic lamp holders, with single-pole, transparent electric wires with double Teflon insulation.


## Light output 1



|                       |         |             |         |
|-----------------------|---------|-------------|---------|
| 1 x Metal halide lamp |         |             |         |
| Nominal lamp power    | 35 W    | Socket      | Gx10    |
| Lamp flux             | 3269 lm | LOR         | 70%     |
| Luminous efficacy     | 65 lm/W | Total flux  | 2273 lm |
| CCT                   | 3000 K  | Total power | 35 W    |
| CRI                   | 84      |             |         |



|                       |         |             |         |
|-----------------------|---------|-------------|---------|
| 1 x Metal halide lamp |         |             |         |
| Nominal lamp power    | 35 W    | Socket      | Gx10    |
| Lamp flux             | 3269 lm | LOR         | 63%     |
| Luminous efficacy     | 59 lm/W | Total flux  | 2075 lm |
| CCT                   | 3000 K  | Total power | 35 W    |
| CRI                   | 84      |             |         |



|                       |         |             |         |
|-----------------------|---------|-------------|---------|
| 1 x Metal halide lamp |         |             |         |
| Nominal lamp power    | 35 W    | Socket      | Gx10    |
| Lamp flux             | 3269 lm | LOR         | 59%     |
| Luminous efficacy     | 55 lm/W | Total flux  | 1942 lm |
| CCT                   | 3000 K  | Total power | 35 W    |
| CRI                   | 84      |             |         |

## Mounting mode

Ceiling recessed

## Electric

System power: 35 W  
Appliance Class: II

**Shape and measurements**

Length: 3.94 in

Width: 3.94 in

Height: 5.51 in

**Adjustability**

Rotatable, Tilttable

**Protection**

IP: 20