
Product data sheet

INSERT+ 3 A26/W 26W 740 GR-94
3100875
PERFORMANCE IN LIGHTING



Part number: 3100875. Serie: INSERT+. Solid and hollow wall recessed luminaire, for indoor and outdoor, comprising : Die-cast aluminium housing and trim, polyester powder coat finish ISO 9227/12944. ISO 9223 (C5) . Extra-clear toughened flat glass diffuser (A26/W versions). Inner satin toughened flat glass diffuser. Anti-ageing custom moulded silicone sealing gasket(s). IP-rated external socket-plug fast connector (QUICK), complete with factory pre-wired cable . Electrical connector for cables Ø 7. Ø 12 mm . Built-in driver. Stainless steel locking hardware. Recessed box to be ordered separately. Supplied with 0,5 m pre-wired H07RN-F cable. Anti-tampering locking kit available as accessory. Available for thourgh wiring as accessories. Connectors fit Ø 7. Ø 10,5 mm and Ø 14. Ø 17 mm cables . Product data | ETIM Group: EG000027. ETIM Class: EC002892. General information | Lampholder: LED. Lightsource lumen output [lm]: 3585. Luminaire lumen output [lm]: 1399. Luminaire wattage [W]: 26 W. Luminous efficacy [lm/W]: 54. CRI: 70. Colour temperature [K]: 4000. Colour / Finishing: GR-94 / Metallic grey / Textured. IP degree of protection: IP66. IK10 20J xx9. Protection class: I. Optic: A26/W - Asymmetric Wide. Net weight [kg]: 2.004. Overall length [mm]: 284. Overall width [mm]: 90. Overall height [mm]: 284. Minimum installation depth [mm]: 105. Mechanical features | Shape: Square 150 x 300 mm. Housing material: Aluminium. Diffuser material: Glass. Electrical features | Voltage type: AC. Input voltage [V AC]: 220/240. Input frequency [Hz]: 50/60. Power factor / COS Φ: 0.9. Inrush current [A/µs]: 5 / 70. C10 1.5 mm²: 41. C16 2.5 mm²: 66. B10 1.5 mm²: 27. B16 2.5 mm²: 44. Installation | Application area: PROFESSIONAL OUTDOOR. Mounting type: Step lighting. Min. ambient temperature [°C]: -20. Max. ambient temperature [°C]: 35. Quick installation. Light features | Lamps: 1. ILCOS: DSL. MacAdam: 5. Lumen maintenance: L80B10@125000h. Distribution of light emission: Direct. Certifications | CE certified. EAC certified. UKCA certified. RCM certified. Mountable on normally inflammable surfaces.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	26 W	CRI	70
Total flux	1399 lm	LOR	100%
Luminous efficacy	54 lm/W	Total power	26 W

Mounting mode

Wall recessed

Shape and measurements

Length: 4.17 in
Width: 12.60 in
Height: 11.18 in

Adjustability

Fixed

Electric

System power: 26 W
Appliance Class: 0

Protection

IP: 66
IK: 10
Designation labels: CE, F