
Product data sheet


AVENUE METRO DIRECT
OPAL_3000MM_BLACK
WHITECROFT



IP 20


1m - Modular linear LED system with a modern minimalist aesthetic for continuous or stand alone applications. Opal optics. Create long lines and angles of light with a seamless aesthetic – as Whitecroft Lighting AVENUE METRO.

Light output 1




1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	3577 lm	ULOR	13%
Luminous efficacy	117 lm/W	Total flux	3577 lm
CCT	3000 K	Total power	30.5 W
CRI	80		




1 x LED

Nominal lamp power	77 W	LOR	100%
Lamp flux	8508 lm	ULOR	13%
Luminous efficacy	110 lm/W	Total flux	8508 lm
CCT	4000 K	Total power	77 W
CRI	80		



1 x LED


Nominal lamp power	77 W	LOR	100%
Lamp flux	8178 lm	ULOR	13%
Luminous efficacy	106 lm/W	Total flux	8178 lm
CCT	3000 K	Total power	77 W
CRI	80		



1 x LED


Nominal lamp power	30 W	LOR	100%
Lamp flux	3730 lm	ULOR	13%
Luminous efficacy	122 lm/W	Total flux	3730 lm
CCT	4000 K	Total power	30.5 W
CRI	80		

Light output 2 (emergency)



1 x LED

Nominal lamp power	1 W	LOR	100%
Lamp flux	339 lm	ULOR	13%
Luminous efficacy	339 lm/W	Total flux	339 lm
CCT	3000 K	Total power	1 W
CRI	80		



1 x LED

Nominal lamp power	1 W	LOR	100%
Lamp flux	359 lm	ULOR	13%
Luminous efficacy	359 lm/W	Total flux	359 lm
CCT	4000 K	Total power	1 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 3.15 in
Width: 118.11 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 31.5-78 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency power supply: Single battery 3 h
Emergency sign: N/A

Protection

IP: 20