



Product data sheet

X-LINE SLIGHT SURFACE LOW UGR LED 1800 LOUVER E 04 840 LINE-S / L-1196MM
19.4306.2321.04
LUXIONA



Indoor luminaire. Assembly: directly mounted to ceiling construction. The body material is aluminum. Colour - RAL 9005 (black). Luminaire dimensions: 1196 x 34 x 68 mm. Diffuser: LOUVER (anti-glare louvre). The efficiency of the optical system is 71,66%. Beam angle: (C0-C180) / (C90-C270) - 46° / 44,6°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 145000 h L90/B10. Luminaire luminous flux: 1336,8 lm. Power of luminaire: 11,3 W. Luminaire's light efficiency: 118,3 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosp: >0,95. Circuit load capacity: 25 (B10), 40 (B16), 39 (C10), 62 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED			
Nominal lamp power	11.3 W	LOR	83%
Lamp flux	1864 lm	Total flux	1556 lm
Luminous efficacy	165 lm/W	Total power	11.3 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 47.09 in
Width: 1.34 in
Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: Black

Glare protection

Glare protection: UGR < 19

Electric

System power: 11.3 W
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F