

# Product data sheet

LOUI 50  
925337.003.76  
RZB




IP  
20

IK  
03

Series: LESS IS MORE 50;system Gerades Einbaumodulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem für Montage in Zwischendecken oder Leichtbau-Hohlwände. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Diffusor(en) aus vergilbungsfreiem Kunststoff (PMMA) opal. Colour: deep black, matt (RAL;9005) Length: 1121;mm Width: 71;mm Height: 1.5;mm Cut-out length: 1128;mm Cut-out width: 60;mm Recess height: 100;mm Luminaire: recess height: 75;mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 28;W Rated luminous flux: 3100;lm Luminous efficiency: 111;lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP;20

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 3000 K |
| Nominal lamp power | 28 W     | CRI         | 80     |
| Total flux         | 3100 lm  | LOR         | 100%   |
| Luminous efficacy  | 111 lm/W | Total power | 28 W   |

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 2.80 in  
Width: 44.13 in  
Height: 0.08 in

## Adjustability

Fixed

## Electric

System power: 28 W

## Protection

IP: 20  
IK: 03