



Product data sheet

INFINITE PRO 1136MM RECESSED OPAL
AK16-34W8PMOS14
LEDSC4



LedsC4 Infinite Pro 1136mm Recessed Opal AK16-34W8PMOS14V1 Lineal lighting system for indoor use. For downlighting. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 2.76 Product length (mm): 1136 Product width or diameter (mm): 75 Product height (mm): 82 Ø of the hole for recessing (mm): 1140x65 Permitted ceiling thickness: 0-25 Class 1. Luminaire not suitable for coating with insulation materials. IP: IN IP20 / OUT IP40. LED. No. of lampholders or LEDs: 1. Driver brand: TRIDONIC. Maximum power of light source: 31.1W. Colour temperature: 3000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 80.000h L80B20. UGR: 23.2. Photobiological risk: RG1. % de Flickering: +/- 5%. Real flux (lm): 4735. Real lm/W: 145. Voltage / frequency range: 220-240/50-60Hz. Voltage: 96. Equipment included: Yes. Total power: 32.6. Power factor: 0.95. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED			
Nominal lamp power	32.6 W	LOR	100%
Lamp flux	4735 lm	Total flux	4735 lm
Luminous efficacy	145 lm/W	Total power	32.6 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted, Standing / Bollard

Shape and measurements

Length: 2.05 in
Width: 44.72 in
Height: 3.54 in

Adjustability

Fixed

Electric

System power: 32.6 W
Appliance Class: I

Protection

IP: 40