
Product data sheet


QUADRO.QUIET GREEN SUSP. ANTHR./SW L DI/ID VDT
T6GH34X-QASWC2930L1N
PLANLICHT



IP 20


LED LO 3000K 91W 7276lm CRI90 https://katalog.planlicht.com/en-gb/fam-quadro/

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	11.38 W	CRI	90
Total flux	910 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	34%
		Total power	11.38 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	11.38 W	CRI	90
Total flux	910 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	34%
		Total power	11.38 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	11.38 W	CRI	90
Total flux	910 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	34%
		Total power	11.38 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	11.38 W	CRI	90
Total flux	910 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	34%
		Total power	11.38 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	11.38 W	CRI	90
Total flux	910 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	34%
		Total power	11.38 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	11.38 W	CRI	90
Total flux	910 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	34%
		Total power	11.38 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	11.38 W	CRI	90
Total flux	910 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	34%
		Total power	11.38 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	11.38 W	CRI	90
Total flux	910 lm	LOR	100%
Luminous efficacy	80 lm/W	ULOR	34%
		Total power	11.38 W

Mounting mode

Pendant

Shape and measurements

Length: 26.38 in
Width: 136.46 in
Height: 2.60 in

Adjustability

Fixed

Electric

System power: 91 W

Protection

IP: 20