Product data sheet


TEMPLED RAYLANCE V3 100 - 90 4000K
385294
TEMPLED



IP 66 IK 08

LED-Hallenleuchte, modularer Gesamtaufbau mit austauschbaren Komponenten (Netzteil, LED-Lichtfelder, Lichtlenkungsoptiken), Leistungsaufnahme: 100 Watt inkl. Vorschaltgerät, Lichtstrom: ca. 18.500 Lumen, Farbtemperatur: 4.000 K, Abstrahlwinkel: 90 Grad, Zhaga-18-Steckplatz für Sensorsysteme, Hochleistungslichtlenkungsoptiken, Schutzart: IP66, Druckausgleichsmembran, 5 Jahre Garantie, 10 Jahre Ersatzteilgarantie, Eingangsspannung AC: 100-240 VAC - 50/60 Hz, Eingangsspannung DC: 127-250 VDC, weitere Daten gemäß Produktblatt. Starre und einstellbare Einfach-, Doppel- und Dreifachhalter mit Ballwurfsicherung optional erhältlich.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	100 W	CRI	80
Total flux	18500 lm	LOR	100%
Luminous efficacy	185 lm/W	Total power	100 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 14.96 in
Width: 13.39 in
Height: 8.27 in

Design

Color of housing: Silver gray

Electric

System power: 100 W
Appliance Class: I

Protection

IP: 66
IK: 08

Other operating numbers

Ambient temperature range: -22...122°F