


Product data sheet

CUBIC MAX RECESSED FRAME - M4
CM40EE-830M-Q910
LIGHTNET



Recessed mounted LED luminaire with surrounding frame for ceilings with cut-out openings. Direct only light distribution. Luminaire body made of aluminium. 7 different diameters from 220mm to 1250mm. Surface white, silver, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Driver integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial $\leq$ MacAdam 3. Colour rendering CRI>80 or CRI>90. Mounting brackets included. Installation in walls not possible. On request: Integration of emergency lighting components, sensor technology, Casambi.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	67 W	CRI	82
Total flux	7620 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	67 W

Mounting mode

Ceiling recessed

Electric

System power: 67 W

Shape and measurements

Length: 35.83 in
Width: 35.83 in
Height: 3.94 in

Protection

Adjustability

Fixed