
Product data sheet

SOLI - 66 93045 DIM5
27123 9335
DELTA LIGHT




Luminaire, low voltage systems low voltage system mounted (indoor use) from Deltalight, named SOLI - 66 93045 DIM5, available in the colour(s): black, white. This luminaire can be used with the following 48V lighting system(s): SOLISCAPE - PROFILE. This luminaire is equipped with LED array 21W / CRI>90 (R9: 52) / 3000K / 2463lm with build-in converter to operate on a voltage of 48V-DC. Dimming protocol: DALI. Light distributor: reflector 45°.

Light output 1




1 x LED

Nominal lamp power	21 W	LOR	73%
Lamp flux	2463 lm	Total flux	1792 lm
Luminous efficacy	117 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	21 W	LOR	73%
Lamp flux	2463 lm	Total flux	1792 lm
Luminous efficacy	117 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	21 W	LOR	73%
Lamp flux	2463 lm	Total flux	1792 lm
Luminous efficacy	117 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	21 W	LOR	73%
Lamp flux	2463 lm	Total flux	1792 lm
Luminous efficacy	117 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	21 W	LOR	73%
Lamp flux	2463 lm	Total flux	1792 lm
Luminous efficacy	117 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	21 W	LOR	73%
Lamp flux	2463 lm	Total flux	1792 lm
Luminous efficacy	117 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	21 W	LOR	73%
Lamp flux	2463 lm	Total flux	1792 lm
Luminous efficacy	117 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	21 W	LOR	73%
Lamp flux	2463 lm	Total flux	1792 lm
Luminous efficacy	117 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	21 W	LOR	73%
Lamp flux	2463 lm	Total flux	1792 lm
Luminous efficacy	117 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	21 W	LOR	73%
Lamp flux	2463 lm	Total flux	1792 lm
Luminous efficacy	117 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		




1 x LED

Nominal lamp power	21 W	LOR	73%
Lamp flux	2463 lm	Total flux	1792 lm
Luminous efficacy	117 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	21 W	LOR	73%
Lamp flux	2463 lm	Total flux	1792 lm
Luminous efficacy	117 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	21 W	LOR	73%
Lamp flux	2463 lm	Total flux	1792 lm
Luminous efficacy	117 lm/W	Total power	24 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant, Contact rail

Shape and measurements

Length: 0.75 in

Width: 3.94 in

Height: 0.91 in

Electric

System power: 24 W

Appliance Class: II

Protection

IP: 20

Designation labels: CE