Product data sheet

FL1200(X)-2AL300-26W-827-40°
FUSION LINEAR SYSTEM
NEKO



IP 20

FUSION Linear profile with two Accent Light inserts as Ceiling mounted / Pendant mounted / Recessed mounted / Trimless recessed mounted; System power 30W; measurement 1200mm x 50mm; after a lifetime of 50000h min. 80% of the luminous flux with energy efficient OSRAM LED Chips; 5 years warranty; narrow beam characteristic with 40° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work according to DIN EN 12464-1 (UGR<19); degree of housing protection according to DIN EN 60529 (IP20)

Light output 1 (integrated)



Lamp type	LED	CCT	2629 K
Nominal lamp power	14.87 W	CRI	93
Total flux	1201 lm	LOR	100%
Luminous efficacy	81 lm/W	Total power	14.87 W

Light output 2 (integrated)



Lamp type	LED	CCT	2629 K
Nominal lamp power	14.87 W	CRI	93
Total flux	1201 lm	LOR	100%
Luminous efficacy	81 lm/W	Total power	14.87 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 47.44 in
Width: 1.89 in
Height: 3.74 in

Adjustability

Fixed

Electric

System power: 29.74 W

Protection

IP: 20