


Product data sheet

RUNDO24 290-260K-10GHM3/830, W
290-260K-10GHM3/830
HALLA




290-260K-10GHM3/830, W Luminaire surface/wall mounted/suspended Material of luminaire: Colour of luminaire: Shape of luminaire: Circular
Size: 630 x 630 x 24 mm Type of installation: Surface, Wall mounted, Suspended Distribution: Direct Optics type: Opal diffuser Protection class:
I Voltage: 220-240V

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	3000 K
Nominal lamp power	1.5 W	CRI	80
Total flux	230 lm	LOR	100%
Luminous efficacy	153 lm/W	Total power	1.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	29.9 W	CRI	80
Total flux	4030 lm	LOR	100%
Luminous efficacy	135 lm/W	Total power	29.9 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Height: 0.94 in
Diameter: 24.80 in

Adjustability

Fixed

Electric

System power: 31.4 W
Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

Protection

IP: 40