Product data sheet

ECLPANELIPSOFT2X1
ECLPANELIPSOFT2X1_5600K_HB_FILTER HD
PROLIGHTS



IP 65

The EclPanel IPSoft2x1 is a 2x1 format IP65 Soft Light, featuring high quality of light in all weather conditions. EclPanel IPSoft range is engineered with a 6-color LED light source controllable in 8 section, maximizing the light flux and delivering a beautiful soft projection with outstanding quality and rich color spectrum. Constructed with durable die-cast magnesium alloy, the IP65 rating of the housing makes the unit water and dust resistant, suitable for challenging environments and sets. The fixture incorporates an onboard power supply and processing unit, facilitating easy setup and operation. It features a 3.5" large display, a user-friendly interface, and comprehensive connectivity options, including both wired and wireless capabilities. Further enhancing its versatility, the unit supports per-section control for custom or desk-created effects. For added portability, the EclPanel IPSoft accepts power via 24-36V batteries and a 48V DC input. Its flexibility extends to control options, compatible with DMX & RDM, Ethernet protocols, remote operation via ControlGo, and wireless CRMX.

Light output 1 (integrated)



Lamp type	LED	CCT	5626 K
Nominal lamp power	522 W	CRI	84
Total flux	64660 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	522 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 2.56 in
Width: 31.81 in
Height: 11.34 in

Adjustability

Tiltable

Electric

System power: 522 W

Protection

IP: 65