


# Product data sheet

LD10238 9.2W 700mA WWB SMB  
LD10238-E3-700-WWB-SMB  
LIGHTGRAPHIX



LD10238 Constant Current surface mount spotlight. 9.2W 700mA 54° Extra wide with Surface Mount Bracket. The LD10238 is a compact, high powered surface mounted spotlight, suitable for use in interior or exterior applications. It can be specified with a wide range of options allowing it to suit most project requirements. Available LED engines include White, Tunable White, CLR LEDs offering multiple outputs, excellent CRIs of 90+ and colour temperatures between 2200K-5000K. A choice of mounting methods, such as a bracket, mount base, tree strap or adjustable ground spike. The use of a matt black inner baffle, recessed LED, single optic and optional honeycomb louvre ensure excellent low glare illumination. With a large selection of paint finishes available and fixing options, the LD10238 can blend discreetly into many environments. This is a very tough, high quality fitting, machined from high grade materials, ensuring excellent thermal and light output performance

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3000 K |
| Nominal lamp power | 9.18 W  | CRI         | 85     |
| Total flux         | 653 lm  | LOR         | 100%   |
| Luminous efficacy  | 71 lm/W | Total power | 9.18 W |

## Mounting mode

Wall mounted, Ceiling mounted, Floor mounted

## Shape and measurements

Height: 2.36 in  
Diameter: 2.36 in

## Adjustability

Rotatable, Tilttable, Free

## Design

Material impression: Aluminum, Glass  
Color of housing: Black, White, Anthracite / graphite, Silver gray

## Electric

System power: 9.18 W  
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI  
Appliance Class: III

## Protection

IP: 67  
Designation labels: CE

## Other operating numbers

Ambient temperature range: -4...95°F