# Product data sheet

LD10238 9.2W 700MA WWB SMB
LD10238-E3-700-WWB-SMB
LIGHTGRAPHIX

IP 67

LD10238 Constant Current surface mount spotlight. 9.2W 700mA 54° Extra wide with Surface Mount Bracket. The LD10238 is a compact, high powered surface mounted spotlight, suitable for use in interior or exterior applications. It can be specified with a wide range of options allowing it to suit most project requirements. Available LED engines include White, Tunable White, CLR LEDs offering multiple outputs, excellent CRIs of 90+ and colour temperatures between 2200K-5000K. A choice of mounting methods, such as a bracket, mount base, tree strap or adjustable ground spike. The use of a matt black inner baffle, recessed LED, single optic and optional honeycomb louvre ensure excellent low glare illumination. With a large selection of paint finishes available and fixing options, the LD10238 can blend discreetly into many environments. This is a very tough, high quality fitting, machined from high grade materials, ensuring excellent thermal and light output performance

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 9.18 W | CRI | 85 |
| Total flux | 653 lm | LOR | 100% |
| Luminous efficacy | 71 lm/W | Total power | 9.18 W |

### Mounting mode

Wall mounted, Ceiling mounted, Floor mounted

### Shape and measurements

Height: 2.36 in
Diameter: 2.36 in

### Adjustability

Rotatable, Tiltable, Free

### Design

Material impression: Aluminum, Glass
Color of housing: Black, White, Anthracite / graphite, Silver gray

### Electric

System power: 9.18 W
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI
Appliance Class: III

### Protection

IP: 67
Designation labels: CE

### Other operating numbers

Ambient temperature range: -4...95°F