

Product data sheet

GUSTAV I (WALL FITTING)
9.744.3066.07
LEIPZIGER LEUCHTEN



IP
55


Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge
Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 125 W | LOR | 54% |
| Lamp flux | 6800 lm | ULOR | 11% |
| Luminous efficacy | 27 lm/W | Total flux | 3648 lm |
| CCT | 3400 K | Total power | 137 W |
| CRI | 54 | | |



1 x High pressure mercury vapour lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 80 W | LOR | 54% |
| Lamp flux | 4000 lm | ULOR | 11% |
| Luminous efficacy | 24 lm/W | Total flux | 2146 lm |
| CCT | 3400 K | Total power | 89 W |
| CRI | 54 | | |

Mounting mode

Wall mounted

Shape and measurements

Height: 9.84 in
Diameter: 9.84 in

Electric

System power: 89-137 W

Protection

IP: 55