

Product data sheet


A-LINE PRO - 16W - 1200MM - ACRYLIC - BROAD DISTRIBUTION - EMERGENCY
EAP016MAB
THORLUX LIGHTING



IP
66

High performance corrosion-resistant luminaires ideal for arduous environments. A-Line Pro luminaires are robust and durable with an aluminium body and die cast ends. Long life silicone sponge gasket ensuring IP66 rating with a choice of acrylic or polycarbonate covers. External mounting brackets and fitted flying lead for easy installation without the need for opening the luminaire. High performance optics with broad or narrow distribution options provide light exactly where it is needed. Cold stores, food factories, public areas, dairies, abattoirs, water treatment works, cable tunnels and multi-story car parks.

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	21 W	CRI	80
Total flux	3130 lm	LOR	100%
Luminous efficacy	149 lm/W	ULOR	6%
		Total power	21 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 51.10 in
Width: 4.76 in
Height: 4.76 in

Adjustability

Fixed

Electric

System power: 21 W

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Protection

IP: 66