Product data sheet

ASY WINK 115 LED GE 2700K SPOT WHITE STRUC 13071009

MODULAR






1 v I ED

1 v I ED



The new Modular recessed spot Not only Wink's technical ingenuity may best be called remarkable, but also its sense of humor. As its name recalls, Wink is a recessed spotlight that likes to wink at you. The straightforward approach, in combination with refined lines and detailed workmanship, results in a fixture that is half hidden in the ceiling and half peeking out. It has all the features to become a new Modular icon. Wink is perfect for any residential or hospitality project, thanks to its symmetric or asymmetric lighting experience. Its identical design allows you to combine both versions, in order to create different lighting effects in the same room.

Light output 1




I X LED	
Nominal lamp power	23.4 W
Lamp flux	1657 lm
Luminous efficacy	56 lm/W
CCT	2700 K
CRI	90

LOR	91%
Total flux	1504 lm
Total power	26.7 W

LOR

Total flux

Total power



I X LLD		
Nominal lamp power	11 W	
Lamp flux	1002 lm	
Luminous efficacy	64 lm/W	
CCT	2700 K	
CRI	90	

+	1 x LED			
-	Nominal lamp power	16.2 W	LOR	91%
7	Lamp flux	1321 lm	Total flux	1199 lm
$\prec \downarrow$	Luminous efficacy	61 lm/W	Total power	19.5 W
\times	CCT	2700 K		
\times	CRI	90		

Mounting mode

Ceiling recessed

91%

909 lm

14.2 W

Shape and measurements

Length: 4.53 in Width: 4.53 in Height: 3.94 in Weight: 0.87 kg

Adjustability

Fixed

Electric

System power: 14.2-26.7 W

Appliance Class: III

Protection

IP: 54