
Product data sheet

RINGO STAR 100MM SUSPENDED - P1
RP1OSE-830M-D3500-U
LIGHTNET




LED pendant luminaire. Direct-indirect or direct-only light distribution. Luminaire body made of aluminium profile with 100mm track width. 13 different diameters from 600mm to 8000mm. Surface silver, white, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90. Height-adjustable central cord suspension or parallel-cord suspension with transparent power supply cable.

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	42 W	CRI	82
Total flux	5280 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	56%
		Total power	42 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	42 W	CRI	82
Total flux	5280 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	56%
		Total power	42 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	42 W	CRI	82
Total flux	5280 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	56%
		Total power	42 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	42 W	CRI	82
Total flux	5280 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	56%
		Total power	42 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	42 W	CRI	82
Total flux	5280 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	56%
		Total power	42 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	42 W	CRI	82
Total flux	5280 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	56%
		Total power	42 W

Light output 7 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	42 W	CRI	82
Total flux	5280 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	56%
		Total power	42 W

Light output 8 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	42 W	CRI	82
Total flux	5280 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	56%
		Total power	42 W

Light output 9 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	42 W	CRI	82
Total flux	5280 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	56%
		Total power	42 W

Light output 10 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	42 W	CRI	82
Total flux	5280 lm	LOR	100%
Luminous efficacy	126 lm/W	ULOR	56%
		Total power	42 W

Mounting mode

Pendant

Shape and measurements

Length: 42.60 in

Width: 3.94 in

Height: 3.94 in

Electric

System power: 420 W

Protection

Adjustability

Height adjustable