

Product data sheet


E04 CEILING ANTHRACITE
E04020
LUCEPLAN



IP
20


Apparecchi a soffitto in due diametri (70 mm e 134 mm) e differenti lunghezze. L'elemento di chiusura, realizzato in alluminio lucidato, in contrasto con la finitura esterna del corpo, conferisce all'oggetto leggerezza evidenziando il dettaglio del sistema di chiusura a filo. La posizione arretrata della sorgente aumenta l'angolo di schermatura e il comfort luminoso.

Light output 1




1 x Halogen low voltage lamp without reflector

Nominal lamp power	75 W	Socket	G53
Lamp flux	850 lm	LOR	99%
Luminous efficacy	11 lm/W	Total flux	840 lm
CCT	3000 K	Total power	75 W
CRI	100		




1 x Halogen low voltage lamp without reflector

Nominal lamp power	50 W	Socket	G53
Lamp flux	560 lm	LOR	100%
Luminous efficacy	11 lm/W	Total flux	560 lm
CCT	3000 K	Total power	50 W
CRI	100		




1 x LED

Nominal lamp power	10 W	Socket	G53
Lamp flux	580 lm	LOR	110%
Luminous efficacy	64 lm/W	Total flux	636 lm
CCT	3000 K	Total power	10 W
CRI	80		



1 x LED

Nominal lamp power	10 W	Socket	G53
Lamp flux	550 lm	LOR	109%
Luminous efficacy	60 lm/W	Total flux	602 lm
CCT	3000 K	Total power	10 W
CRI	80		



1 x Halogen low voltage lamp without reflector

Nominal lamp power	75 W	Socket	G53
Lamp flux	840 lm	LOR	100%
Luminous efficacy	11 lm/W	Total flux	838 lm
CCT	3000 K	Total power	75 W
CRI	100		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 5.27 in

Width: 5.27 in

Height: 14.65 in

Adjustability

Fixed

Electric

System power: 10-75 W

Protection

IP: 20