


Product data sheet

RECESSED DOWNLIGHT NOVO 2 ROUND INNER RING SET BACK ROUND 15.4W 1900LM CRI > 90 3000K 43MA W
2010.9862 - NOVO2 RD SB CR125 LED1900-930-R27 WH ONF
REGENT



Recessed downlight Novo 2 Round inner ring set back, with LED, system power: 15.4 W, luminous flux of luminaire 1900 lm, colour rendering index CRI > 90, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L90 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, rated current: 43 mA, direct light emission, housing in die-cast aluminium, with ceiling trim, white, RAL 9016, with reflector, 27, 1 integral control gear, ON/OFF, high-quality die-cast aluminium housing, reduced installation time thanks to fully pre-assembled luminaire, including connection to control gear, with through-wiring option, suitable for ceiling thicknesses from 1 to 45 mm protection class II, ingress protection IP20 / IP44, glow wire test 850 °C, impact strength: IK 07 this product contains a light source of energy efficiency class D and EPREL registration number: 2026444 Ø = 140 mm, ceiling cutout ø 125 mm up to 135 mm, ET = 103 mm,

Light output 1



1 x LED			
Nominal lamp power	8.2 W	LOR	100%
Lamp flux	1900 lm	Total flux	1899 lm
Luminous efficacy	232 lm/W	Total power	15.4 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 0.04 in
Width: 0.04 in
Height: 0.04 in
Weight: 0.799 kg

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 15.4 W
Appliance Class: II

Protection

IP: 44
IK: 07