Product data sheet


LD151 9.2W 700MA WB
LD151-E3-700-WB
LIGHTGRAPHIX



IP 67 IK 08

LD151 Ø81mm Recessed Uplight. Constant Current. 9.2W 700mA 34° Wide beam. The LD151 is a powerful uplight with a compact size and depth, designed specifically to produce low glare illumination onto interior and exterior walls and columns. It can be specified with a wide range of options allowing it to suit most project requirements. Available LED engines include E3, Tunable White, RGBW and F1 which offer a range of colour temperatures between 2200K-5000K and beam angles, with multiple accessories and bezel finishes to choose from. The bezel aesthetic is minimal featuring black trim glass and no visible fixings. This is a very tough, high quality fitting, machined from high grade materials, ensuring excellent thermal and light output performance.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9.18 W	CRI	85
Total flux	647 lm	LOR	100%
Luminous efficacy	70 lm/W	Total power	9.18 W

Mounting mode

Floor recessed

Shape and measurements

Height: 2.95 in
Diameter: 3.19 in

Adjustability

Fixed

Design

Material impression: Matt, Bronze, Glass, Brass, Gloss, Stainless steel
Color of housing: Black, White, Anthracite / graphite, Silver gray

Electric

System power: 9.18 W
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI
Appliance Class: III

Protection

IP: 67
IK: 08
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...77°F