


Product data sheet

PRO-STRADA MINI, 18LEDS OPTIEK 4
41361X3X
PROLUMIA




Light Source: Cree / Lumileds / Samsung / Osram Color temperature: 3000K / 4000K Color rendering index: Ra ≥ 70 Operating temperature: -30°C ~ +50°C Rated life hours: L90 > 100.000 hours 300-500mA LED driver (included): Philips Xitanium SR programmable / 1-10V / Dali Input: 220-240V AC 50/60Hz Power factor: > 0,95

Light output 1




1 x LED

Nominal lamp power	19.2 W	LOR	100%
Lamp flux	2400 lm	Total flux	2400 lm
Luminous efficacy	125 lm/W	Total power	19.2 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	21.2 W	LOR	100%
Lamp flux	2800 lm	Total flux	2800 lm
Luminous efficacy	132 lm/W	Total power	21.2 W
CCT	4000 K		
CRI	80		




1 x LED


Nominal lamp power	22.4 W	LOR	100%
Lamp flux	2800 lm	Total flux	2800 lm
Luminous efficacy	125 lm/W	Total power	22.4 W
CCT	3000 K		
CRI	80		




1 x LED			
Nominal lamp power	19.7 W	LOR	100%
Lamp flux	2600 lm	Total flux	2600 lm
Luminous efficacy	132 lm/W	Total power	19.7 W
CCT	4000 K		
CRI	80		




1 x LED			
Nominal lamp power	18.2 W	LOR	100%
Lamp flux	2400 lm	Total flux	2400 lm
Luminous efficacy	132 lm/W	Total power	18.2 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	16.7 W	LOR	100%
Lamp flux	2200 lm	Total flux	2200 lm
Luminous efficacy	132 lm/W	Total power	16.7 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	17.6 W	LOR	100%
Lamp flux	2200 lm	Total flux	2200 lm
Luminous efficacy	125 lm/W	Total power	17.6 W
CCT	3000 K		
CRI	80		



1 x LED			
Nominal lamp power	20.8 W	LOR	100%
Lamp flux	2600 lm	Total flux	2600 lm
Luminous efficacy	125 lm/W	Total power	20.8 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted, Pole top mounted

Shape and measurements

Length: 22.87 in

Width: 12.09 in

Height: 4.25 in

Electric

System power: 16.7-22.4 W

Appliance Class: 0

Protection

IP: 66

IK: 08

Designation labels: CE, ENEC