


# Product data sheet

CLARA IV (CLEAR ATTACHMENT)  
9.764.2032.05  
LEIPZIGER LEUCHTEN



For medium/high light requirements, mounting height 4.00 – 5.00 m. - Impact-resistant clear/opal polycarbonate attachment,UV- stabilized - High-pressure lamps with coated bulbs use reflector lamellae made of premium highest-grade aluminium, burnishid and anodized, for light guidance and glare limitation - Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on one block - Adapter jack connection -Available in any RAL or DB colour without surcharge - for post dia. 76mm; order post dia.76mm separately (see standard poles from p. 258) -With adapter for concrete pole consisting of flange plate made of hot galvanized steel, and transition piece made of corrosionresistant cast aluminium

## Light output 1



### 1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	53%
Lamp flux	5600 lm	ULOR	11%
Luminous efficacy	36 lm/W	Total flux	2989 lm
CCT	2000 K	Total power	83 W
CRI	25		

## Mounting mode

Pole top mounted

## Electric

System power: 83 W

## Shape and measurements

Height: 22.83 in

Diameter: 29.53 in