Product data sheet


PRAGUE 2 BOLLARD
PRA-10012-ME-W40
LIGMAN



IP 65 IK 08

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing, frame and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - High-efficiency PMMA lens - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13.9 W	CRI	80
Total flux	1542 lm	LOR	100%
Luminous efficacy	111 lm/W	ULOR	100%
		Total power	13.9 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 6.89 in
Width: 7.87 in
Height: 39.37 in
Weight: 8.7 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 13.9 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C