


Product data sheet


NOTOR 78 DELTA 70-30 ANOD CONT 4K
13185-402
FAGERHULT



IP
20

Installation Designed for single or continuous installation via a wire pendent and special loops that give flexible c-c spacing. Special loops included in the delivery. Wires suspension are ordered separately. Connection The start luminaire is supplied with 2,4 m mains cable excluding plug as standard. With additional numbers -448, -449 and -474 is the luminaire equipped with 2,4 mains cable, 3x1,0 mm² and earthed plug. The connecting mains cable comes out on the same side as the pull switch. The luminaire unit is equipped with a through-wiring cable (5x1.5 mm²) and a snap-in connection in each end cap. In a continuous installation, the luminaire row should always begin with a start luminaire. Design Body in white (RAL 9016) or natural anodised, extruded aluminium finish. The top is covered by an active film which generates a broad light pattern and which works as a dust cover. Louvre Delta - microprism louvre in acrylic (PMMA). Reflectors The louvres act as reflectors. Dimming DALI/phase-pulse control as standard. Additional number is only available with single installation.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	87 W	CRI	80
Total flux	10302 lm	LOR	100%
Luminous efficacy	118 lm/W	ULOR	30%
		Total power	87 W

Mounting mode

Pendant

Electric

System power: 87 W

Shape and measurements

Length: 91.93 in
Width: 3.07 in
Height: 3.07 in

Protection

IP: 20

Adjustability

Fixed

Design

Color of housing: White