



# Product data sheet

INS230LED-0600-J2-1-35E-33-21P20-GRP-PC-ZB-AM01  
32-232-06J204  
ATM LIGHTING




Waterproof and dustproof industrial LED light fitting compatible with central battery. The housing is made of fiber glass reinforced polyester (GRP) and the diffuser is made of UV stabilised polycarbonate or PMMA. | Certificates: CNBOP, PZH | Emergency luminous flux: 2706lm | Weight: 3.2kg | Ambient temperature range: -25÷50°C

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	18.2 W	CRI	80
Total flux	2706 lm	LOR	100%
Luminous efficacy	149 lm/W	ULOR	3%
		Total power	18.2 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	18.2 W	CRI	80
Total flux	2706 lm	LOR	100%
Luminous efficacy	149 lm/W	ULOR	3%
		Total power	18.2 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 27.56 in

Width: 7.48 in

Height: 5.08 in

## Adjustability

Fixed

## Electric

System power: 36.4 W

Ballast: ECG

Suitable for feed-through wiring

Appliance Class: I

## Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

## Design

Material impression: Matt

Color of housing: White

Designer: Michał Ramczykowski

## Protection

IP: 67

IK: 08

Designation labels: CE

## Other operating numbers

Ambient temperature range: -13...122°F